

KDebugDialog

David Faure



KDebugDialog

Contents

KDebugDialog

KDebugDialog is a dialog box for managing diagnostic messages at runtime. It features a simple and a full mode.

In order to be able to make changes **Disable all debug output** has to be unchecked.

Simple mode

If you simply start **kdebugdialog**, you will see a list of 'areas', that can be disabled or enabled. A `kDebug(area)` call in the code will show something in the debug output only if the area is enabled.

NOTE

Note that `kWarning`, `kError` and `kFatal` always appear, they are *NOT* controlled by this setting.

Enter a matching string into the **Search** box at the top of the list, this allows you to filter the areas which are displayed in the list view. Use the buttons below the list to select or deselect all items in the view (the other areas are not effected) or change the debug output for a single item using the check box in front of it.

Full mode

If you start **kdebugdialog** `--fullmode`, then for every severity level you can define separately what should be done with the diagnostic messages of that level, and the same for each debug area.

In full mode, first you should select the debug area you are interested in from the list at the left of the dialog using the search box at the top of the list.

You may independently set the output for various types of messages:

- **Information**
- **Warning**
- **Error**
- **Fatal Error**

For each of these types, you can set the following:

Output to:

In this Combobox, you can choose where the messages should be output. The choices are: 'File', 'Message Box', 'Shell' (meaning `stderr`) and 'Syslog'. Please do not direct fatal messages to `syslog` unless you are the system administrator yourself. The default is 'Shell'.

Filename:

This is only enabled when you have chosen 'File' as the output and provides the name of that file (which is interpreted as relative to the current folder). The default is `kdebug.dbg`.

Apart from this, you can also tick the check box **Abort on fatal errors**. In this case, if a diagnostic message with the severity level `KDEBUG_FATAL` is output, the application aborts with a `SIGABRT` after outputting the message.

When you close the dialog by pressing **OK**, your entries apply immediately and are saved in `~/.config/kdebugrc`. When you press **Cancel**, your entries are discarded and the old ones are restored.

Credits to Kalle Dalheimer for the original version of KDebugDialog

This documentation is licensed under the terms of the [GNU Free Documentation License](#).